

AP-6000

Advanced multiparameter water quality probe with self cleaning

The AP-6000 can be used for comprehensive spot monitoring as part of a package or it can be used in permanent deployments thanks to its new, much smaller self cleaning mechanism. It features a diameter of only 55mm (the same size as the AP-5000) making it our smallest self cleaning Aquaprobe to date.

Build

All Aquaprobes are made with the same marine grade aluminium, finished in black with hard anodising for excellent corrosion and biofouling resistance. The use of metal, as opposed to plastic, gives our products their characteristic weight and high quality look and feel.

Sensors

The AP-6000 comes with all of the common water quality testing sensors pre fitted to the probe:

pH • ORP • Conductivity • TDS • SSG • Resistivity • Salinity
• Dissolved Oxygen • Depth • Temperature

Probes come with 4 empty sockets

The AP-6000 comes with four empty Aux sockets pre-fitted with removable blanking plugs. These sockets allow you to customise your probe by adding in additional sensors. Each socket can house either an Ion Selective Sensor (ISE) or any of our optical sensors



AP-6000 fitted with 2 ISE sensors and 2 optical sensors

New smaller self cleaning system



AP-6000 with additional sensors removed exposing central cleaning shaft

The AP-6000's removable self cleaning system fits into the probe body via a socket and screw collar. The small shaft houses a small but powerful motor that allows the two brushes to rotate and clean all fitted sensors, as seen above.

The main advantages of the AP-6000 are its versatility and its price point. The Aquaprobe is small enough to be used portably as part of a package including carry case, but it can also be used with an Aqualogger or with telemetry if you require a more determinant monitoring solution.

Cleaning control

The wiper cleaning frequency can be configured when used with an Aqualogger. When used with a telemetry system the wiper will run every 6 hours to reduce battery drain.



AP-6000 Package

Package comes complete with Aquaprobe, GPS Aquameter, 3m cable, rugged case and accessories. Various cable lengths are available; 10, 20 and 30m as standard.



All cables 20m and over come on a winding reel making them much easier to operate, especially when profiling.

GPS Aquameter

The GPS Aquameter is a hand held device with a display for live data viewing and data recording. As one of our flagship products it is included in every Aquaprobe package. GPS coordinates are recorded everytime you take a reading. It is designed to be very simple to use and to make your job easier in the field.



AP-6000 Flowcell

The flowcell for the AP-6000 uses an adaptor that must first be fitted to the probe under the probe sleeve. A flow rate of 30 Litres/hour is ideal, Recommended operating pressure is 500mB.

This eliminates air contact with pumped samples from groundwater boreholes allowing truly representative measurements to be obtained.



AquaLink

Our AquaLink software is free to download from our website's download section. Use this software to download recorded data from your Aquameter, for analysis, reporting and google map creation.

AquaLink Features

- Simple data download via button
- Tick and un-tick datasets to customise your outputs
- Output a text report for all highlighted data
- Output data as a CSV file that you can open in Excel
- Output data as a .KML file for use in Google Earth



Specifications

Protection Class	IP68 (permanent immersion)
Immersion Depth	Min 75mm. Max 100m *
Operating Temperature	-5 °C - +70 °C
Dimensions (L x Dia)	340mm x 58mm
Weight	950g

* 100m submersion for period of 12 hours, 30m submersion suitable for permanent deployment, depth measurement displayed up to 60m on Aquameter.

Standard Parameters	Parameter	Range	0 - 500.0% / 0 - 50.00 mg/L	
		Dissolved Oxygen	Resolution	0.1% / 0.01 mg/L
		Accuracy	0 - 200%: ± 1% of reading, 200% - 500%: ± 10%	
Depth AP-2000/ AP-5000	Range	± 0 - 60.00 m (60m max displayed depth, max probe immersion 100m)		
	Resolution	1 cm		
	Accuracy	± 0.5% FS		
Depth AP-7000	Range	± 0 - 99.99 m		
	Resolution	1 cm		
	Accuracy	± 0.2% FS		
Conductivity (EC)	Range	0 - 200 mS/cm (0 - 200,000 µS/cm)		
	Resolution	3 Auto-range scales: 0 - 9999 µS/cm, 10.00 - 99.99 mS/cm, 100.0 - 200.0mS/cm		
	Accuracy	± 1% of reading		
TDS*	Range	0 - 100,000 mg/L (ppm)		
	Resolution	2 Auto-range scales: 0 - 9999mg/L, 10.00 - 100.00g/L		
	Accuracy	± 1% of reading		
Resistivity*	Range	5 Ω • cm - 1 MΩ • cm		
	Resolution	2 Auto-range scales: 5 - 9999 Ω • cm, 10.0 - 1000.0 KΩ • cm		
	Accuracy	± 1% of reading		
Salinity*	Range	0 - 70 PSU / 0 - 70.00 ppt (g/Kg)		
	Resolution	0.01 PSU / 0.01 ppt		
	Accuracy	± 1% of reading		
Seawater Specific Gravity*	Range	0 - 50 st		
	Resolution	0.1 st		
	Accuracy	± 1.0 st		
pH	Range	0 - 14 pH / ± 625mV		
	Resolution	0.01 pH / ± 0.1mV		
	Accuracy	± 0.1 pH / ± 5mV		
ORP	Range	± 2000mV		
	Resolution	0.1mV		
	Accuracy	± 5mV		
Temperature (non freezing)	Range	-5°C - +50°C (23°F - 122°F)		
	Resolution	0.01°C / 0.1°F		
	Accuracy	± 0.5 °C		

* Readings calculated from EC and temperature electrode values

ISE	Parameter	Range	0 - 9,000mg/L (ppm)	
		Ammonium	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 - 8,999.9 mg/L
		Accuracy	± 10% of reading or 2ppm (whichever is greater)	
Ammonia†	Range	0 - 9,000mg/L (ppm)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 - 8,999.9 mg/L		
	Accuracy	± 10% of reading or 2ppm (whichever is greater)		
Chloride	Range	0 - 20,000mg/L (ppm)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 - 19,999.9 mg/L		
	Accuracy	± 10% of reading or 2ppm (whichever is greater)		
Fluoride	Range	0 - 1,000mg/L (ppm)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 - 999.9 mg/L		
	Accuracy	± 10% of reading or 2ppm (whichever is greater)		
Nitrate	Range	0 - 30,000mg/L (ppm)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 - 29,999.9 mg/L		
	Accuracy	± 10% of reading or 2ppm (whichever is greater)		
Calcium	Range	0 - 2,000mg/L (ppm)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 - 1,999.9 mg/L		
	Accuracy	± 10% of reading or 2ppm (whichever is greater)		

† Ammonium electrode required. Readings calculated from ammonium, pH and temperature values.

Optical	Parameter	Range	0 - 3000 NTU	
		Turbidity	Resolution	2 Auto-range scales: 0.0 - 99.9 NTU, 100 - 3000 NTU
		Accuracy	± 5% of auto-ranged scale	
Chlorophyll	Range	0 - 500.0 µg/L (ppb)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 µg/L, 100.0 - 500.0 µg/L		
	Repeatability	± 5% of reading		
Phycocyanin (freshwater BGA)	Range	0 - 300,000 cells/mL		
	Resolution	1 cell/mL		
	Repeatability	± 10% of reading		
Phycerythrin (marine BGA)	Range	200,000 cells/mL		
	Resolution	1 cell/mL		
	Repeatability	± 10% of reading		
Rhodamine WT Dye	Range	0 - 500 µg/L (ppb)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 µg/L, 100.0 - 500.0 µg/L		
	Accuracy	± 5% of reading		
Fluorescein Dye	Range	0 - 500 µg/L (ppb)		
	Resolution	2 Auto-range scales: 0.00 - 99.99 µg/L, 100.0 - 500.0 µg/L		
	Accuracy	± 5% of reading		
Refined Oil	Range	0 - 10,000 µg/L (ppb) (Naphthalene)		
	Resolution	0.1 µg/L		
	Repeatability	± 10% of reading		
CDOM / FDOM	Range	0 - 20,000 µg/L (ppb) (Quinine Sulphate)		
	Resolution	2 Auto-range scales: 0.0 - 9,999.9 µg/L, 10,000 - 20,000 µg/L		
	Repeatability	± 10% of reading		

The accuracy figures quoted throughout this document represent the equipment's capability at the calibration points at 25°C. These figures do not take into account errors introduced by variations in the accuracy of calibration solutions and errors beyond the control of the manufacturer that may be introduced by environmental conditions in the field. Accuracy in the field is also dependent upon full calibration and minimal time between calibration and use.